





## ENCLOSURE CONSTRUCTION NOTES:

- FABRICATED FROM 1/8" ALUMINUM SHEET STOCK ELECTRICALLY WELDED AND REINFORCED WHERE REQUIRED.
- 2. CONSTRUCTION WILL BE NEMA 3R AND 12, RAINTIGHT AND DUST TIGHT.
- 3. ALL NUTS, BOLTS, SCREWS AND HINGES SHALL BE STAINLESS STEEL.
- 4. NUTS, BOLTS & SCREWS SHALL NOT BE VISIBLE FROM OUTSIDE OF ENCLOSURE.
- 5. PHENOLIC NAMEPLATES SHALL BE PROVIDED AS REQUIRED.
- 6. CONTROL WIRING SHALL BE MARKED AT BOTH ENDS BY PERMANENT WIRE MARKERS.
- 7. A PLASTIC COVERED WIRING DIAGRAM SHALL BE ATTACHED TO THE INSIDE OF THE FRONT DOOR.
- 8. ENCLOSURE WILL BE FACTORY WIRED AND CONFORM TO REQUIRED NEMA STANDARD.
- 9. FINISH: ANODIZED ALUMINUM
- 10. PANEL SHALL BE TESCO TYPE III AF OR APPROVED EQUAL.



DRAWN BY: M. LEE
CHECKED BY: D. PITTON
APPROVED BY: T. SUPAN
DATE: AUGUST 2006

TRAFFIC SIGNAL POWER PANEL

TR-3

CITY OF SANTA CLARA

PAGE: 40